

**DUNHAM AIR COLLET CLOSER
MODEL DACCOM16C/3J
ASSEMBLY AND OPERATING INSTRUCTIONS**

Specification:

Maximum pull force: 3040 lbs. @ 100 P.S.I. (30.4 X line pressure).

Maximum push force: 1200 lbs. @ 100 P.S.I. (12.0 X line pressure).

Maximum stroke : 5/16"

Maximum RPM : 4300 (continuous)
6000 (intermittent)

Largest diameter: 7.88"

Length : 8.20" open (without spindle adapter)
8.51" closed

Weight : 37 lbs. (without spindle adapter)

Through hole : 16C: 1.625 or 3J: 1.75" (thru the drawtube)

Compressed air requirements:

Actuation: Variable 40 to 120 P.S.I.; clean, dry air required;

Lubrication/Cooling: 15 P.S.I.; clean, lubricated

NOT REQUIRED ON ROTARY TABLE APPLICATIONS

Lubrication: Mobil "DTE" Light (or equivalent):

NOT REQUIRED ON ROTARY TABLE APPLICATIONS

Description:

This Dunham air powered rotary actuator operates at up to 4300 RPM, even when powered with maximum air pressure. Special consideration has been given to enhance its durability; this includes hardened wear surfaces, complete sealing of rotating components, and urethane wipers. The bearings are shielded, positive air pressure moves throughout the actuator, and the drawtube mount acts as a seal.

The air actuator is designed to mount to rotating devices, most commonly spindles. The unit will provide a push or pull force capable of opening or closing collets, fixtures, and short stroke power chucks.

Installation:

1) Spindle Mounting Adapter:

Spindle Adapter may need to be further machined to fit spindle end. The blank adapter (MB244-16C) has adequate length to fit into various mount positions. The adapter should be shortened if possible to allow the actuator to mount as close to the spindle as possible. Precision bore the spindle adapter inside diameter to fit the outboard end of spindle. The actuator mounting surface of the adapter must measure at least .001" T.I.R. perpendicular with the spindle when mounted.

Thread the inside diameter of the adapter if the outboard end of the spindle has threads.

Drill and tap four equally spaced holes for 1/4-20 set screws. The set screws will clamp the adapter to the spindle.

2) Fastening Drawtube to Actuator:

The drawtube is now installed into the air actuator. Tighten the four 3/8"-16 socket head set screws so their half dog points engage the drilled 1/4" holes. The screws must then be loosened 1/8 turn. Drawtube installation is now complete.

3) Adjusting Actuator Concentricity:

Adjust four bolts (face mount to mounting adapter) to finger-tightness. Reduce air pressure supplied to forward port of actuator to 15 P.S.I. Using a dial indicator reach to indicator the rear most diameter surface. Rotate spindle slowly to measure the rise and fall of this portion of the actuator. Adjust concentricity by tapping the main bearing mount lightly. If actuator is in good alignment with the spindle, the indicator should measure .0005"-.0010" concentricity. Tighten four bolts securely.

4) Attached Oil-Mist Lubrication:

To operate actuator to full potential, attaching the oil-mist lubricator assembly is required. The unit supplied must be mounted close to actuator while providing easy access to the oil reservoir. Attach oil-mist to lubricator ports (10-32). A shut off valve **MUST** be used to turn off air supplied to oil-mist assembly when not in use.

FAILURE TO USE THIS LUBRICATION MAY RESULT IN UNIT FAILURE. The air regulator should be adjusted to 15 P.S.I. The Norgren "Type L07 Lubricator" should be adjusted to supply 1 drop every 40 seconds. The reservoir should be replenished with Mobil "DTE" light (or equivalent) as required. A small amount of grease is displaced out of the bearings by the rotation and the oil-mist lubricator; this should be considered normal.

NOT REQUIRED ON ROTARY TABLE APPLICATIONS

Operating Instructions:

Inserting Collet:

- 1) With piston in forward or released position, back off locking key, enabling drawtube to be turned by knurled collet adjusting knob.
- 2) Place collet in spindle. Turn knurled knob clockwise until taper of collet engages with taper of spindle.
- 3) Align locking key with adjusting slot (4 slots provided) on draw tube, engage locking key. This prevents drawtube from turning and becoming loose during operation.

How to control holding force:

- 1) By using the regulator and gage, start with air pressure of 40 lbs.; increase pressure gradually until part is held sufficiently for machining operation.
- 2) The Dunham Air Actuator permits even gripping pressure although workpiece may have diameter variation. Holding force can be adjusted for any type of machining by increasing or decreasing the air pressure.

Maintenance:

- 1) Little or no maintenance is required. Bearings are self lubricating. All components such as bearings, "O" ring seals and retaining rings are standard.

Installing an air cleaner and lubricator in line is advisable, but not essential.

*****SAFETY*****

The purchaser or end user of this retrofit unit is fully responsible for the fabrication and application of special protective guarding to cover this unit's moving parts. Drawtube cutoff must be performed as instructed above. Oil must be available for the oil-mist system.

FAILURE TO COMPLETE THE PROPER INSTALLATION AS INSTRUCTED ABOVE CAN RESULT IN OPERATOR INJURY OR PREMATURE WEAR ON THE UNIT.

MANUALS/AIR COLLET CLOSER INSTRUCTIONS MODEL DACCOM16C/3J