


MATERIAL: NEOPRENE 60 DUROMETER EXTRUSION

*NOTE: CRITICAL DIMENSION

A	10/24/2022	UPDATED .125 ± .005 TO .125 ± .008	JL	UNLESS OTHERWISE SPECIFIED: DIMENSIONS ARE IN INCHES TOLERANCES: FRACTIONAL ± 1/64 ANGULAR: ± 1° TWO PLACE DECIMAL ± .015 THREE PLACE DECIMAL ± .005 SURFACE FINISH 32 Ra BREAK ALL SHARP CORNERS DO NOT SCALE DRAWING
B	3/28/2023	UPDATED .125 TOLERANCE TO ±.027 AND .046 TOLERANCE TO ±.015	JL	
REV.	DATE	CHANGES	BY	

	NAME	DATE	<div> THE DUNHAM TOOL COMPANY DIVISION OF LISLE CORPORATION</div> <div>TITLE: FLAP SEAL</div>		
DRAWN	JL	10/24/2022			
CHECKED					
MATERIAL	NOTED				
0:	FINISH		<div><div>SIZE</div><div>A</div></div> <div><div>DWG. NO.</div><div>D050-DFS</div></div> <div><div>REV</div><div>B</div></div>		
	HEAT TREAT				
	<div>PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF THE DUNHAM TOOL COMPANY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF THE DUNHAM TOOL COMPANY IS PROHIBITED.</div>				
			SCALE: 10:1 WEIGHT:		SHEET 1 OF 1